

# FTA 600R

## FOLDING ARM ACTUATOR

### OPENING STROKE SIZES

93° (programmable)

### PUSH FORCE

600 N

### VOLTAGE


24V DC (+/- 10%)



### DESCRIPTION

The FTA 600R folding arm actuator has been developed for installation on side-hung inward or outward opening windows or doors. The roller arm is designed for use on doors used for day-day access. Supplied with potential-free contact used for control of an electric door-opener or a bolt lock. Folding arm drives can be used in SHEV systems and as well as for natural ventilation via automated windows, mainly in façades. Opening stroke is programmable (in factory) - 0-93°. Fixing brackets sold separately.

### WINDOW TYPES



### APPLICATION



### COLOURS

- Silver Anodised
- ⊗ Custom RAL colour

### CERTIFICATION



## TECHNICAL DATA

Voltage	24V DC (+/- 10%)
Push Force	600 N
Pull Force	600 N
Opening Stroke	93° (programmable)
Opening Speed	2,0°/sec
Current Consumption	1.4 A
Operating Conditions	-5°C - +75°C
Switch-on Duration	30 % (ON: 3 min. / OFF: 7 min.)
Colour	Silver Anodised or custom RAL colour
IP Rating	IP 32
Life Span	10,000 opening and closing movements
Delivery Includes	1 x Actuator (fixing brackets sold separately)
Flex Length	3 m
Cable Dimensions	2-Core (plus 3 communication wires)
Min. window width	> 600 mm (Side-Hung)
Max. window width	< 1200 mm (Side-Hung)
Synchronisation	Yes (programmable)

## ACCESSORIES


FTA600R-524156 - Bracket Set

## PART CODES

FTA600R - FTA 600R Actuator 24 V 90° Silver

FTA600R-2 - FTA 600R Actuator (synchronised) 24 V 90° Silver

## DIMENSIONS



## CONTROLS



**WSC 204**  
AOV Control Unit



**WSK 320**  
Override Switch




**SSR-D**  
Smoke Sensor



**WSC 310**  
AOV Control Unit

## BRACKET TYPES



FA600-524156