

|           |                                      |
|-----------|--------------------------------------|
| Sizes     | Bespoke                              |
| Free Area | 1m <sup>2</sup> or 1.5m <sup>2</sup> |

# SV-W-GL2

The SV-W-GL2 Glazed Louvre Window was developed for optimized smoke ventilation. It combines good tightness with attractive architectural effect when insulated glazing is not necessary.



## Blades

Single glass 8, 10 or 12mm thickness. Alternative infill types are available including timber, aluminium or stone panels.



## Certification

Certified and tested in accordance to EN 12101-2



## Applications

- » End of Corridor
- » Head of Stairwell

## Technical Data

|                     |   |
|---------------------|---|
| Frame               | Aluminium profiles, thermal broken                            |
| Blades              | Insulated glass   Solid infill                                |
| Geometric Free Area | 1m <sup>2</sup> or 1.5m <sup>2</sup> (depending on vent size) |
| Voltage             | 24V DC  |
| Opening             | 84°   |
| Opening Speed       | > 60 secs   |
| Current Consumption | 0.7 Amp   |
| Colour              | Custom RAL colour   |
| Certification       | EN 12101-2  |
| Cable Dimension     | 2-Core  |
| Delivery Includes   | 1 x Vent & 1 x Actuator                                       |

## Dimensions

